

BT Strand Woven Product Specification



Eco Flooring Systems Pty Ltd

ABN:151 277 605 82

Ph: **02 9410 0640** Fax: 02 9410 0447

Mob: 0425 240 279

E-mail: bamboo@ecoflooring.com.au

Exclusive supplier of BT Strand

BT Strand bamboo is made from random strips of bamboo assembled under extreme pressure to create the hardest most durable bamboo flooring available.

This unique looking floor is perfect for domestic high traffic areas where harder surfaces are a requirement and hardwood or bamboo floors have been specified.

Applications

Interior use commercial and domestic. BT Strand is not designed for exterior applications, bathrooms or "wet areas"

Technical Specifications

Dimensions:

BT Strand Lock

130mm(W)x14mm(T)x1845mm (L)

BT Strand T & G

Coffee & Natural

137mm(W)x14mm(T)x1830mm(L)

Colours:

Natural – light colour

Coffee – dark colour

White – stained finish / Lock only

Strand Milling:

Patented Locking System

Tongue and Groove on all sides

Micro bevel to top edges

Coatings:

Satin aluminium oxide

Finished with 13 layer Treffert coating system.

Incorporating:

Hydro UV Barrier Coat

UV Duro Sealer

UV Sandable Sealer

HPC Anti scratch Top coat

BT Strand Accessories:

Quad 19mm x 19mm x 1830mm

Reducer 48mm x 14mm x 1830mm

Stair Nose 96mm x 14mm x 1830mm

Scotia 19mm x 19mm x 1830mm

Accessories by the piece 1830mm length

Packing:

BT Strand Lock

6 pieces/box 1.44m²

Weight: Approx 21kg per box

BT Strand T&G

6 pieces/box 1.50 m²

Weight: Approx 22kg per box

Warranty:

25 year structural warranty – Domestic

10 year structural warranty - Commercial

Hardness Comparison:

Natural 14.3kN

Coffee 15.3kN.

White 14.3kN

Moisture Content:

8-10%

Density:

1100-1300kg/m³

Formaldehyde Emission:

< E1, 0.0155 ppm (Below recommended World Health Organization levels.)

Quality Standards:

The supplier of BT strand flooring is ISO 9001 certified, CE certified, FSC



Installation:

BT Strand – Lock floating floor

BT Strand – T & G Direct Stick installation

Flooring to be installed in accordance with Eco Flooring Systems Pty Ltd Installation instructions

Maintenance:

Refinishable

Contact:

Eco Flooring Systems Pty Ltd

ABN: 151 277 605 82

Ph: **02 9410 0640** Fax: 02 9410 0447

Mob: 0425 240 279

E-mail: bamboo@ecoflooring.com.au

www.ecoflooring.com.au